

# AGRIMAX V-FLECTO

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TYRE SIZE</b>    | <b>VF 520/85 R 50</b>                                                                    |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / HIGH-POWER TRACTOR                                                             |
| <b>VERSION</b>      | STEEL BELTED                                                                             |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 177 D                                                                                    |



## DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94517008 | <b>RC (IN)</b> | 255.6            |
| <b>SW (IN)</b>  | 21.1     | <b>RIM REC</b> | DW 18 L          |
| <b>OD (IN)</b>  | 85.0     | <b>RIM ALT</b> | DW 16 L          |
| <b>SLR (IN)</b> | 38.3     | <b>ECE</b>     | E11-106R-0011305 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI                     | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|-------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45                            | 6880  | 7900  | 9070  | 10240 | 11410 | 12590 | 13760 | 14640 |
| FROM 40 TO 25                 | 7560  | 8690  | 9980  | 11260 | 12540 | 13830 | 15120 | 16090 |
| 20                            | 7700  | 8860  | 10170 | 11490 | 12800 | 14110 | 15420 | 16410 |
| 12                            | 7860  | 9030  | 10370 | 11710 | 13050 | 14380 | 15720 | 16730 |
| 5                             | 8310  | 9560  | 10970 | 12390 | 13800 | 15220 | 16630 | 17700 |
| *UPTO 5 CYC WITH FRONT LOADER | 10590 | 12170 | 13980 | 15770 | 17580 | 19380 | 21190 | 22530 |
| 5HT                           | 7700  | 8860  | 10170 | 11490 | 12800 | 14110 | 15420 | 16410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.