


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 12.5/80 - 18 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 129 A8 |
| LI/SS FREE ROLLING | 142 A8 |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CODICE USA | 94018789 | RC (IN) | 113.9 |
| SW (IN) | 12.1 | RIM REC | W 9 |
| OD (IN) | 38.9 | RIM ALT | 9; 11 |
| SLR (IN) | 17.2 | ECE | E4-106R-001904 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 54 |
|-----------|------|
| 5 FR | 8180 |
| 15 FR | 6960 |
| 20 FR | 6550 |
| 25 FR | 5840 |
| 5 DW | 5710 |
| 15 DW | 4850 |
| 20 DW | 4560 |
| 25 DW | 4080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.