


AGRIMAX RT 657

| | |
|---------------------|--|
| TYRE SIZE | 440/65 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 138 D ; 141 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94042753 | RC (IN) | 127.6 |
| SW (IN) | 17.4 | RIM REC | W 14 L |
| OD (IN) | 42.5 | RIM ALT | W 13; W 15 L |
| SLR (IN) | 18.9 | ECE | E4-106R-000760 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2450 | 2870 | 3280 | 3650 | 4010 | 4320 | 4790 | 5200 |
| 30 | 2580 | 3010 | 3450 | 3840 | 4210 | 4540 | 5040 | 5470 |
| 25 | 2680 | 3130 | 3580 | 3980 | 4380 | 4720 | 5220 | 5680 |
| 20 | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |
| 5 LT | 3280 | 3850 | 4400 | 4890 | 5380 | 5800 | 6430 | 6980 |
| 5 HT | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.