


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>900/55 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D ; 181 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	880	<b>RIM REC</b>	DW 27 B
<b>OD (MM)</b>	1950	<b>RIM ALT</b>	DW 30 B
<b>SLR (MM)</b>	880	<b>ECE</b>	E11-106R-006946
<b>RC (MM)</b>	5842	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
<b>65</b>	3255	3800	4265	4805	5350	5890	6590	7055	7750
<b>50</b>	3420	3990	4480	5050	5620	6190	6920	7410	8140
<b>40</b>	3465	4045	4540	5115	5695	6270	7015	7510	8250
<b>30</b>	3745	4370	4905	5530	6155	6780	7580	8115	8915
<b>10 LT</b>	4365	5090	5715	6440	7170	7895	8830	9455	10385
<b>10 HT</b>	3745	4370	4905	5530	6155	6780	7580	8115	8915

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.