

AGRIMAX RT 765

TIRE SIZE	360/70 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	122 D



РАЗМЕРЫ US STANDARD

USA CODE	94063130	RC (IN)	133.7
SW (IN)	14.1	RIM REC	W 11
OD (IN)	45.4	RIM ALT	W 10; W 12
SLR (IN)	20.4	ECE	E11-106R-005824

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	1820	2120	2410	2710	3010	3310
30	1920	2230	2540	2850	3160	3470
25	2000	2330	2660	2980	3310	3630
20	2090	2440	2780	3120	3460	3800
5 LT	2450	2840	3240	3640	4030	4430
5 HT	2090	2440	2780	3120	3640	3800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.