

# AGRIMAX RT 765

|                     |                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>200/70 R 16</b>                                                                          |
| <b>UM</b>           | US STANDARD                                                                                 |
| <b>CONSTRUCTION</b> |  RADIAL    |
| <b>MACHINERY</b>    | PULVÉRISATEUR / TRACTEUR /<br>MACHINE À VENDANGER /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE |
| <b>VERSION</b>      | STANDARD                                                                                    |
| <b>TIRE TYPE</b>    | TL                                                                                          |
| <b>LI/SS</b>        | 94 A8/B                                                                                     |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94026869 | <b>RC (IN)</b> | 81.1           |
| <b>SW (IN)</b>  | 7.8      | <b>RIM REC</b> | W 6            |
| <b>OD (IN)</b>  | 27.0     | <b>RIM ALT</b> | W 7            |
| <b>SLR (IN)</b> | 12.4     | <b>ECE</b>     | E4-106R-000607 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9   | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|-----|------|------|------|------|------|------|------|
| <b>30</b>   | 690 | 800  | 930  | 1040 | 1160 | 1280 | 1380 | 1480 |
| <b>25</b>   | 690 | 800  | 930  | 1040 | 1160 | 1280 | 1380 | 1480 |
| <b>20</b>   | 750 | 860  | 990  | 1110 | 1250 | 1370 | 1480 | 1590 |
| <b>5 LT</b> | 940 | 1080 | 1230 | 1390 | 1550 | 1710 | 1850 | 1980 |
| <b>5 HT</b> | 750 | 860  | 990  | 1110 | 1250 | 1370 | 1480 | 1590 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.