

AGRIMAX FORCE

TIRE SIZE	IF 380/80 R 38
UM	US STANDARD
MACHINERY	ERNTemaschine / HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	149 D



ABMESSUNGEN US STANDARD

USA-CODE	94062140	RIM REC	W 12
SW (IN)	15.0	RIM ALT	W 11 ; W 13
OD (IN)	61.9	ECE	E11-106R-005715
SLR (IN)	28.5	TRA CODE	R1W
RC (IN)	188.7	TREAD DEPTH (32 nd)	56.07

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	3050	3520	4030	4560	5080	5600	6130	6510
FROM 40 TO 25	3360	3870	4440	5020	5590	6160	6730	7165
20	3490	4020	4620	5210	5810	6400	7000	7450
12	3630	4180	4790	5410	6030	6650	7260	7740
5	4270	4910	5630	6360	7090	7810	8540	9090
*UPTO 5 CYC WITH FRONT LOADER	4710	5410	6220	7020	7810	8620	9420	10030
5HT	3490	4020	4620	5210	5810	6400	7000	7450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.