


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 600/600 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	595	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1584	<b>RIM ALT</b>	DW 18 L; DW 21 B
<b>SLR (MM)</b>	691	<b>ECE</b>	E11-106R-008773
<b>RC (MM)</b>	4710	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2250	2620	2985	3355	3725	4095
<b>FROM 65 TO 40</b>	2475	2880	3285	3690	4095	4500
30	2520	2935	3350	3760	4175	4590
20	2570	2995	3415	3835	4255	4680
10	2720	3165	3610	4055	4500	4950
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3465	4030	4595	5165	5730	6300
10HT	2520	2935	3350	3760	4175	4590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.