

# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>420/90 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	147 A8/B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	DW13
<b>OD (MM)</b>	1518	<b>RIM ALT</b>	W 14 L
<b>SLR (MM)</b>	684	<b>ECE</b>	E11-106R-006021
<b>RC (MM)</b>	4571	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4
50	1665	2155	2645	2895	3075
40	1665	2155	2645	2895	3075
30	1780	2310	2835	3100	3295
10	2495	3235	3970	4340	4615

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.