


AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 155 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94063284 | RC (IN) | 188.5 |
| SW (IN) | 18.9 | RIM REC | W 15 L |
| OD (IN) | 62.2 | RIM ALT | W 14 L; W 16 L |
| SLR (IN) | 28.7 | ECE | E11-106R-005834 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 47 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 40 | 3340 | 3940 | 4530 | 5050 | 5640 | 6150 | 6760 | 7260 | 7950 | 8540 |
| 30 | 3510 | 4130 | 4760 | 5300 | 5930 | 6470 | 7100 | 7630 | 8360 | 8970 |
| 25 | 3660 | 4310 | 4960 | 5520 | 6180 | 6750 | 7400 | 7960 | 8710 | 9360 |
| 20 | 3840 | 4530 | 5210 | 5810 | 6490 | 7090 | 7770 | 8370 | 9150 | 9830 |
| 5 LT | 4480 | 5270 | 6070 | 6770 | 7560 | 8260 | 9050 | 9740 | 10660 | 11450 |
| 5 HT | 3840 | 4530 | 5210 | 5810 | 6490 | 7090 | 7770 | 8370 | 9150 | 9830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.