


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>710/55 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94060023	<b>RC (IN)</b>	174.9
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	58.8	<b>ECE</b>	E11-106R-005940
<b>SLR (IN)</b>	26.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
<b>30</b>	4300	4960	5620	6390	7050	7830	8710	9370	10250	11020
<b>25</b>	4300	4960	5620	6390	7050	7830	8710	9370	10250	11020
<b>20</b>	4610	5310	6020	6840	7550	8380	9330	10030	10980	11790
<b>10 CYC</b>	7100	8190	9280	10550	11640	12920	14370	15460	16920	18190
<b>5 CYC</b>	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.