



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 42



PRODUCT DATA SHEET



Radial



Performance



Traction



Durability



EARTHMAX SR 42

RADIAL OTR TIRES

EARTHMAX SR 42 is a radial OTR tire specially engineered for haul trains in mining and logging applications. The distinctive tread design provides outstanding traction and lateral stability as well as good braking and cornering performance on rough and gravel terrains even on ice and snow. Indeed, the special cut-and-wear-resistant tread compound is particularly suitable in extreme cold climate. EARTHMAX SR 42 features an All Steel casing for excellent durability and a long service life.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 24"	14.00 R 24	TL	E-4	***	171 B	CRC	105	380	1412	652	4231	38	10.00 W	-
Ø 25"	14.00 R 25	TL	E-4	***	171 B	CRC	105	380	1412	652	4231	38	10.00/1.5	-
	14.00 R 25	TL	E-4	***	171 B	CRC	105	380	1412	652	4231	38	10.00/2.0	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference