


# EARTHMAX SR 31

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>29.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | CHARGEUR / BULLDOZER /<br>TOMBREAU ARTICULÉ / CHARGEUR /<br>BULLDOZER                    |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 216 A2   |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>CODE USA</b> | 94054398 | <b>RIM REC</b>     | 25.00/3.5 |
| <b>OD (IN)</b>  | 73.3     | <b>TRA CODE</b>    | L3        |
| <b>SLR (IN)</b> | 32.2     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 218.7    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 41900 | 43000 | 44100 | 45400 | 46700 | 49400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.