


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 D



РАЗМЕРЫ IS STANDARD

SW (MM)	710	RIM REC	DW 25 B
OD (MM)	1930	RIM ALT	DW 23 B; MW 25 B
SLR (MM)	860	ECE	E11-106R-002998
RC (MM)	5786	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3250	3785	4315	4850	5380	5915
FROM 65 TO 40	3575	4160	4745	5330	5915	6500
30	3645	4240	4835	5435	6030	6630
20	3715	4325	4930	5540	6150	6760
10	3930	4575	5215	5860	6505	7150
*UPTO 10 CYC WITH FRONT LOADER	5005	5820	6640	7460	8280	9100
10HT	3645	4240	4835	5435	6030	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.