


AGRIMAX SPARGO

TIRE SIZE	VF 480/80 R 46 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	177 D



РАЗМЕРЫ US STANDARD

USA CODE	94519026	RC (IN)	232.6
SW (IN)	18.9	RIM REC	DW 16 L
OD (IN)	76.2	RIM ALT	DW 15 L
SLR (IN)	35.1	ECE	E11-106R-004756-01

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17.5	20.5	23.5	26	29	32	35	38	41	44	47	49	52
45	8190	9080	9960	10390	10980	11270	11570	12150	12740	13180	13760	14200	14640
FROM 40 TO 25	9010	9980	10940	11420	12070	12390	12710	13350	14000	14490	15130	15610	16100
20	9190	10180	11160	11660	12310	12640	12970	13620	14280	14780	15430	15920	16420
12	9370	10380	11380	11880	12550	12880	13220	13880	14550	15060	15720	16230	16740
5*	9910	10970	12040	12570	13280	13630	13980	14690	15400	15930	16640	17170	17710
UPTO 10 CYC.	38980	35190	32105	30735	29085	28335	27620	26295	25085	24235	23210	22495	21810
UPTO 20 CYC.	32645	29470	26880	25745	24355	23730	23135	22020	20995	20300	19440	18835	18265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.