


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 340/85 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 133 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94033072 | RC (IN) | 183.8 |
| SW (IN) | 13.9 | RIM REC | W 12 |
| OD (IN) | 60.7 | RIM ALT | W 11 |
| SLR (IN) | 28.0 | ECE | E4-106R-000766 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 2500 | 2910 | 3320 | 3730 | 4130 | 4540 |
| 25 | 2500 | 2910 | 3320 | 3730 | 4130 | 4540 |
| 20 | 2680 | 3120 | 3550 | 3990 | 4430 | 4860 |
| 5 LT | 3360 | 3900 | 4450 | 5000 | 5560 | 6100 |
| 5 HT | 2680 | 3120 | 3550 | 3990 | 4430 | 4860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.