

# FL 252

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>7.00 - 12</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TT   |



## DIMENSIONS US STANDARD

|                 |          |           |    |
|-----------------|----------|-----------|----|
| <b>USA CODE</b> | 94006892 | <b>PR</b> | 14 |
| <b>SW (IN)</b>  | 7.6      |           |    |
| <b>OD (IN)</b>  | 26.9     |           |    |
| <b>RIM REC</b>  | 5.00 S   |           |    |

## LOAD CAPACITY (LBS/TYRE)

| <b>MPH / PSI</b>          | <b>131</b> |
|---------------------------|------------|
| <b>15 LOAD WHEEL</b>      | 6075       |
| <b>15 STEER WHEEL</b>     | 4675       |
| <b>5 OTHER VEHICLES</b>   | 6075       |
| <b>15 OTHER VEHICLES</b>  | 4675       |
| <b>STATIC SIDE LOADER</b> | 7055       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.