

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>210/95 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	108 A8/B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	214	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	855	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	385	<b>ECE</b>	E4-106R-00634
<b>RC (MM)</b>	2565	<b>SRI</b>	400

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	470	540	620	700	780	860	930	1000
40	470	540	620	700	780	860	930	1000
30	505	580	665	750	835	925	1000	1070
10 LT	630	725	835	940	1050	1155	1250	1340
10 HT	505	580	665	750	835	925	1000	1070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.