

# CON STAR

**380/75 - 20****UM** IS STANDARD**CONSTRUCTION**  BIAS**MACHINERY** KÜÇÜK YÜKLEYİCİ / TELESKOPIK  
YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /  
TELESKOPIK YÜKLEYİCİ**VERSION** INDUSTRIAL**TIRE TYPE** TL

148 A8



## UNDEFINED IS STANDARD

|                 |      |                |                                       |
|-----------------|------|----------------|---------------------------------------|
| <b>SW (MM)</b>  | 385  | <b>RIM REC</b> | W 12                                  |
| <b>OD (MM)</b>  | 1080 | <b>RIM ALT</b> | W 11; 12 SDC; 12; W 13; 13 SDC;<br>13 |
| <b>SLR (MM)</b> | 500  | <b>ECE</b>     | E11-106R-003022                       |
| <b>RC (MM)</b>  | 3273 |                |                                       |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 40                | 3150        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.