

FL 630 SUPER

TIRE SIZE	600/55 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ESPALHADOR / CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
VERSÃO	HD
TIRE TYPE	TL
LI/SS	177 D



DIMENSÕES IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1333	ECE	E11-106R-003005
SLR (MM)	604	SRI	625
RC (MM)	4104		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	1825	2265	2705	3285	3800	4380	4965	5330	5915	6500	6865	7300
50	2210	2740	3270	3980	4595	5305	6010	6450	7160	7865	8305	8835
40	2485	3080	3675	4470	5165	5960	6755	7250	8045	8840	9335	9930
30	2760	3420	4080	4965	5735	6615	7500	8050	8935	9815	10365	11025
25	2885	3580	4270	5195	6000	6925	7845	8425	9345	10270	10845	11535
10	3285	4075	4865	5915	6835	7885	8940	9595	10645	11695	12355	13140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.