


MULTIMAX MP 522



TIRE SIZE	480/80 R 26 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	160 A8/B

DIMENSIONS US STANDARD

USA CODE	94052707	RC (IN)	168.8
SW (IN)	18.9	RIM REC	DW 15 L
OD (IN)	56.2	RIM ALT	DW 16 L
SLR (IN)	25.1	ECE	E11-106R-002970

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	32	35	38	41	44	46	49	52
30	5750	6750	7340	7840	8330	8830	9420	9920	-	-
25	5750	6750	7340	7840	8330	8830	9420	9920	-	-
20	6160	7220	7860	8390	8920	9460	10090	10610	-	-
15	6390	7500	8160	8710	9260	9810	10470	11010	-	-
5 CYC.	7000	8630	9380	10120	11010	11760	12500	13390	14140	14880
STATIC	10720	13240	14380	15520	16890	18030	19170	20530	21680	22820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.