


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>480/80 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94040827	<b>RC (IN)</b>	221.6
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	74.4	<b>RIM ALT</b>	DD 16 L; W 16 L
<b>SLR (IN)</b>	33.7	<b>ECE</b>	E4-106R-001481

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	4190	4870	5560	6240	6920	7600
25	4190	4870	5560	6240	6920	7600
20	4490	5210	5950	6680	7420	8150
5 LT	5610	6530	7450	8370	9280	10200
5 HT	4490	5210	5950	6680	7420	8150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.