

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>320/85 R 34</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | SPECIAL                                                               |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 141 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94047239 | <b>RC (IN)</b> | 168.5          |
| <b>SW (IN)</b>  | 13.0     | <b>RIM REC</b> | W 11           |
| <b>OD (IN)</b>  | 55.4     | <b>RIM ALT</b> | W 9 ; W 10     |
| <b>SLR (IN)</b> | 25.4     | <b>ECE</b>     | E4-106R-000758 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   |
|-------------|------|------|------|------|------|------|------|------|------|
| <b>30</b>   | 2050 | 2390 | 3130 | 3810 | 4140 | 4430 | 4830 | 5220 | 5680 |
| <b>25</b>   | 2050 | 2390 | 3130 | 3810 | 4140 | 4430 | 4830 | 5220 | 5680 |
| <b>20</b>   | 2190 | 2560 | 3350 | 4080 | 4440 | 4750 | 5180 | 5600 | 6080 |
| <b>5 LT</b> | 2740 | 3210 | 4200 | 5100 | 5570 | 5940 | 6480 | 7010 | 7620 |
| <b>5 HT</b> | 2190 | 2560 | 3350 | 4080 | 4440 | 4750 | 5180 | 5600 | 6080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.