


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>240/70 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	104 A8/B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	244	<b>RIM REC</b>	W8
<b>OD (MM)</b>	742	<b>RIM ALT</b>	W 8 L ; W 9
<b>SLR (MM)</b>	340	<b>ECE</b>	E11-106R-007531
<b>RC (MM)</b>	2213	<b>SRI</b>	350

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	425	490	560	630	705	775	850	900
40	425	490	560	630	705	775	850	900
30	455	525	600	680	755	830	910	965
10 LT	570	655	755	850	945	1045	1140	1210
10 HT	455	525	600	680	755	830	910	965

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.