


# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>340/80 R 20 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	144 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	11
<b>OD (MM)</b>	1052	<b>RIM ALT</b>	W10; 11 SDC; W11; 12; 12 SDC
<b>SLR (MM)</b>	483	<b>ECE</b>	E11-106R-003957
<b>RC (MM)</b>	3176	<b>SRI</b>	500

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1345	1600	1820	2075	2325	2495	2800	-	-
40	1345	1600	1820	2075	2325	2495	2800	-	-
30	1440	1710	1950	2220	2490	2670	3000	-	-
25	1495	1775	2025	2305	2585	2770	3110	-	-
10 CYC.	1640	2020	2375	2730	3110	3385	3825	4035	4200
STATIC	2515	3095	3640	4190	4770	5185	5865	6185	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.