


# AGRIMAX RT 657

<b>TYRE SIZE</b>	<b>320/65 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	117 D ; 120 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94042036	<b>RC (IN)</b>	97.1
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	32.4	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (IN)</b>	14.4	<b>ECE</b>	E4-106R-001815

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	1330	1570	1790	1980	2180	2360	2610	2830
30	1400	1640	1880	2080	2290	2480	2740	2980
25	1450	1700	1950	2160	2380	2570	2840	3090
20	1540	1800	2060	2290	2510	2710	3010	3260
5 LT	1800	2090	2400	2670	2930	3160	3510	3800
5 HT	1540	1800	2060	2290	2510	2710	3010	3260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.