



US standard



GROWING TOGETHER

# TRAC FARM



PRODUCT DATA SHEET



Bias



A8



Technologies



More Lugs



Extra Deep Tread

Performance



Durability



Self-Cleaning



Traction



High Load Capacity



Cut and Chip Resistance



# TRAC FARM

TRAC FARM is a heavy-duty tire specifically designed for tractors in soil tillage and haulage applications. Its deep tread and the special cut-and-chip-resistant compound make the tire suitable for the most difficult operating conditions, ensuring the best return on investment during the entire product life-cycle. TRAC FARM has been designed with more lugs providing extraordinary traction and self-cleaning properties.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 20"	94043415	11.2 - 20	W 10	W 9	11.4	39.4	18.2	115.7	45	71	STD	8	TT	107 A8
	94040841	12.4 - 28	W 11	W 9; W 10	12.6	51.0	23.7	153.1	47	118	STD	10	TT	121 A8
	94040322	12.4 - 28	W 11	W 9; W 10	12.6	51.0	23.7	153.1	47	118	STD	12	TT	122 A8
Ø 28"	94040155	13.6 - 28	W 12	W 11	14.4	53.0	24.6	158.8	50	137	STD	12	TT	124 A8
	94040889	16.9 - 28	W 15 L	W 14 L	17.3	56.5	26.1	166.1	51	193	STD	12	TT	139 A8
	94042395	18.4 - 30	W 16 L	W 15 L	18.4	61.0	28.2	179.4	55	245	STD	12	TT	145 A8
Ø 30"	94049905	18.4 - 30	W 16 L	W 15 L	18.5	61.6	28.2	179.4	55	258	HD	14	TT	147 A8
	94043743	18.4 - 30	W 16 L	W 15 L	18.5	61.6	28.2	179.4	55	256	STD	14	TT	147 A8

STD: Standard - HD: Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference