

EARTHMAX SR 44

| | |
|---------------------|--------------------|
| TIRE SIZE | 325/95 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | ON/OFF TRUCK |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 158 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|-------|--------------------|-------|
| OD (MM) | 1250 | RIM ALT | 9.00V |
| SLR (MM) | 575 | TRA CODE | E4 |
| RC (MM) | 3790 | STAR RATING | ★★★ |
| RIM REC | 8.50V | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 3075 | 3150 | 3350 | 3450 | 3550 | 3650 | 3750 | 3875 | 4000 | 4125 | 4250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.