


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 650/75 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	651	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1941	<b>RIM ALT</b>	DW 21 B
<b>SLR (MM)</b>	866	<b>ECE</b>	E11-106R-007385
<b>RC (MM)</b>	5802	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2955	3395	3895	4400	4900	5405	5905	6280
<b>FROM 65 TO 40</b>	3245	3730	4280	4830	5385	5935	6490	6900
30	3375	3880	4455	5030	5605	6175	6750	7180
20	3505	4030	4625	5220	5815	6415	7010	7455
10	4120	4735	5435	6140	6840	7540	8240	8765
<b>UPTO 30 CYC</b>	4220	4845	5565	6280	7000	7715	8435	8970
<b>UPTO 15 CYC</b>	5030	5780	6635	7490	8345	9200	10055	10695
<b>UPTO 10 CYC</b>	5515	6335	7275	8215	9150	10090	11030	11730
10 HT	3375	3880	4455	5030	5605	6175	6750	7180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.