

# FLOTATION 648

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	128 A8/124 B
<b>LI/SS FREE ROLLING</b>	140 A8/136 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	510	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	945	<b>ECE</b>	E4-106R-002713
<b>SLR (MM)</b>	416	<b>PR</b>	10
<b>RC (MM)</b>	2750		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.70	2.00
10 FR	2960	3185	3500
20 FR	2665	2865	3150
30 FR	2370	2550	2800
40 FR	2115	2275	2500
50 FR	1905	2050	2240
10 DW	2130	2290	2520
20 DW	1915	2060	2270
30 DW	1700	1830	2015
40 DW	1520	1635	1800
50 DW	1370	1470	1600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.