


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 250/80 R 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 125 A8 ; 125 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 250 | RIM REC | W 8 |
| OD (MM) | 835 | RIM ALT | W 7 ; W 9 |
| SLR (MM) | 375 | ECE | E11-106R-006605 |
| RC (MM) | 2539 | SRI | 410 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|--------------|-----|-----|------|------|------|------|------|------|------|------|------|------|
| 50 | 580 | 680 | 780 | 875 | 975 | 1060 | 1175 | 1240 | 1355 | 1470 | 1570 | 1650 |
| 40 | 580 | 680 | 780 | 875 | 975 | 1060 | 1175 | 1240 | 1355 | 1470 | 1570 | 1650 |
| 30 | 620 | 730 | 835 | 940 | 1045 | 1135 | 1260 | 1330 | 1455 | 1580 | 1685 | 1770 |
| 10 LT | 780 | 910 | 1045 | 1175 | 1310 | 1420 | 1575 | 1665 | 1820 | 1975 | 2105 | 2215 |
| 10 HT | 620 | 730 | 835 | 940 | 1045 | 1135 | 1260 | 1330 | 1455 | 1580 | 1685 | 1770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.