

# RM 2002

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>11.00 - 20</b>                             |
| <b>UM</b>           | IS STANDARD                                   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | RIMORCHIO / ATTREZZI AGRICOLI /<br>GRU MOBILE |
| <b>VERSIONE</b>     | STANDARD                                      |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONI IS STANDARD

|                |          |           |    |
|----------------|----------|-----------|----|
| <b>SW (MM)</b> | 302      | <b>PR</b> | 16 |
| <b>OD (MM)</b> | 1101     |           |    |
| <b>RIM REC</b> | 8.0      |           |    |
| <b>RIM ALT</b> | 7.5; 8.5 |           |    |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>7.95</b> | <b>7.25</b> |
|-------------------|-------------|-------------|
| <b>100 LS</b>     | 3250        | -           |
| <b>100 LD</b>     | -           | 2900        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.