

# AGRIMAX TERIS

**IF 580/80 R 34 CFO**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / PAMUK TOPLAMA MAKINESİ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	177 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	586	<b>RIM REC</b>	DW 20 B; DW 20 A
<b>OD (MM)</b>	1792	<b>RIM ALT</b>	DW 21 A; DW 21 B
<b>SLR (MM)</b>	810	<b>ECE</b>	E4-106R-001833
<b>RC (MM)</b>	5422	<b>SRI</b>	850

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
70	2460	2860	3260	3725	4120	4520	4985	5250	5785	6250	6645
<b>FROM 65 TO 40</b>	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
30	2815	3270	3725	4225	4710	5165	5700	6005	6610	7140	7595
20	2920	3395	3865	4420	4890	5365	5915	6230	6860	7415	7885
10	3435	3990	4545	5195	5755	6310	6960	7330	8070	8720	9275
<b>UPTO 30 CYC*</b>	3515	4085	4655	5315	5885	6455	7210	7500	8260	8925	9490
<b>UPTO 15 CYC*</b>	4190	4870	5545	6340	7020	7695	8490	8940	9845	10640	11315
10 HT	2815	3270	3725	4225	4710	5165	5700	6005	6610	7140	7595

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.