

# AW 09

<b>TIRE SIZE</b>	<b>320/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	OUTILLAGE AGRICOLE / REMORQUE / PRESSE À PAILLE / MOISSONNEUSE / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	133 A8
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94037834	<b>RC (IN)</b>	103.9
<b>SW (IN)</b>	12.2	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	35.5	<b>ECE</b>	E4-106R-000378
<b>SLR (IN)</b>	15.4		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6360
15 DW	5400
20 DW	5080
25 DW	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.