


FLOTATION 648

TIRE SIZE	700/50 - 22.5
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	168 A8/164 B



ABMESSUNGEN IS STANDARD

SW (MM)	700	RIM REC	24.00
OD (MM)	1270	ECE	E4-106R-002270
SLR (MM)	550	PR	12
RC (MM)	3775		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.60	1.80
10 FR	7050	7315	7840
20 FR	6345	6585	7055
30 FR	5640	5850	6270
40 FR	5035	5225	5600
50 FR	4530	4705	5000
10 DW	5035	5230	5600
20 DW	4530	4705	5040
30 DW	4025	4185	4480
40 DW	3595	3735	4000
50 DW	3235	3360	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.