


# RIDEMAX IT 697 (M+S)

|              |  |
|--------------|--|
| TIRE SIZE    | 460/70 R 24 IND  |
| UM           | IS STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRATTORE   |
| VERSIONE     | STANDARD   |
| TIRE TYPE    | TL   |
| LI/SS        | 157 A8 ; 152 D   |



## DIMENSIONI IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 465  | RIM REC | DW 15 L         |
| OD (MM)  | 1254 | RIM ALT | DW14 L; DW 16L  |
| SLR (MM) | 571  | ECE     | E11-106R-006840 |
| RC (MM)  | 3772 | SRI     | 600             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 1775 | 2170 | 2380 | 2805 | 3160 | 3550 |
| 50         | 1920 | 2340 | 2570 | 3030 | 3415 | 3835 |
| 40         | 2065 | 2520 | 2765 | 3260 | 3675 | 4125 |
| 30         | 2130 | 2600 | 2855 | 3370 | 3795 | 4260 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.