


FLOTATION 558

TIRE SIZE	400/55 - 22.5
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / VÉHICULE CITERNE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	138 A8/134 B
LI/SS FREE ROLLING	150 A8/146 B



DIMENSIONS IS STANDARD

SW (MM)	405	RIM REC	AG 11.75
OD (MM)	1020	RIM ALT	12.25; 13.00; AG 13.00
SLR (MM)	445	ECE	E4-106R-002261
RC (MM)	3084	PR	14

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.20	3.50
10 FR	4285	4450	4690
20 FR	3855	4005	4220
30 FR	3425	3560	3750
40 FR	3060	3180	3350
50 FR	2755	2860	3000
10 DW	3015	3135	3305
20 DW	2715	2820	2975
30 DW	2415	2510	2645
40 DW	2155	2240	2360
50 DW	1940	2015	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.