

# AW 702

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / ATTREZZI AGRICOLI / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI / RIMORCHIO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94009671	<b>RC (IN)</b>	111.3
<b>SW (IN)</b>	12.1	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	38.0	<b>RIM ALT</b>	11
<b>SLR (IN)</b>	17.0	<b>ECE</b>	E4-106R-001906

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>62</b>
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.