


# CON STAR

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>480/80 - 26</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS  |
| <b>MACHINERY</b>    | PALA COMPATTA / SOLLEVATORE<br>TELESCOPICO / PALA COMPATTA /<br>SOLLEVATORE TELESCOPICO |
| <b>VERSIONE</b>     | INDUSTRIAL  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 160 A8  |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94052813 | <b>RC (IN)</b> | 168.2           |
| <b>SW (IN)</b>    | 19.3     | <b>RIM REC</b> | DW 15 L         |
| <b>OD (IN)</b>    | 55.5     | <b>RIM ALT</b> | DW 16 L         |
| <b>SLR (IN)</b>   | 25.3     | <b>ECE</b>     | E11-106R-003033 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>46</b> |
| 25               | 9920      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.