

# SKID POWER HD (B)

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | <b>18X8.5 - 10</b> |
| <b>UM</b>           | US STANDARD        |
| <b>CONSTRUCTION</b> | ⊠ BIAS             |
| <b>MACHINERY</b>    | KOMPAKTHJULLASTARE |
| <b>VERSION</b>      | IMPLEMENT          |
| <b>TIRE TYPE</b>    | TL                 |
| <b>LI/SS</b>        | 82 A8              |



## DIMENSIONER US STANDARD

|                 |          |                |                             |
|-----------------|----------|----------------|-----------------------------|
| <b>USA CODE</b> | 94055937 | <b>RC (IN)</b> | 54.0                        |
| <b>SW (IN)</b>  | 8.1      | <b>RIM REC</b> | 7.00 I - 55; I - 70; I - 90 |
| <b>OD (IN)</b>  | 18.3     | <b>ECE</b>     | E11-106R-003536             |
| <b>SLR (IN)</b> | 8.4      | <b>PR</b>      | 8                           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>44</b> |
| 25               | 1047      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.