


AGRIMAX ELOS

TIRE SIZE	520/85 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	169 A8 ; 169 B



DIMENSIONES US STANDARD

CÓDIGO USA	94070503	RC (IN)	247.8
SW (IN)	20.9	RIM REC	DW 16 L
OD (IN)	81.7	RIM ALT	DW 15 L; DW 18 L; W 15 L; W 16 L; W18 L; DD 16 L; DD 18 L
SLR (IN)	37.7	ECE	E11-106R-007935

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
30	4990	5890	6780	7550	8440	9210	10110	11130	12030	12790
25	4990	5890	6780	7550	8440	9210	10110	11130	12030	12790
20	5350	6300	7260	8080	9040	9870	10820	11920	12870	13690
5 LT	6690	7890	9090	10120	11320	12350	13550	14910	16110	17140
5 HT	5350	6300	7260	8080	9040	9870	10820	11920	12870	13690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.