


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>800/65 R 32 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / COLHEDORA DE ALGODÃO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8 ; 175 B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	818	<b>RIM REC</b>	DW 27 B
<b>OD (MM)</b>	1853	<b>RIM ALT</b>	DW 25 B ; DH 27 B
<b>SLR (MM)</b>	838	<b>ECE</b>	E4-106R-001430
<b>RC (MM)</b>	5551	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3175	3660	4485	4900	5455	5865	6420	6900
40	3450	3975	4875	5325	5925	6375	6975	7500
30	3695	4255	5220	5700	6340	6825	7465	8025
15 CYC	5695	6560	8045	8790	9780	10520	11510	12375
10 CYC	6210	7155	8775	9585	10665	11475	12555	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.