


# AGRIMAX ELOS

	<b>520/85 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	169 A8 ; 169 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	2075	<b>RIM ALT</b>	DW 15 L ;DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L
<b>SLR (MM)</b>	957	<b>ECE</b>	E11-106R-007935
<b>RC (MM)</b>	6293	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	2265	2670	3075	3425	3830	4180	4585	5050	5455	5800
40	2265	2670	3075	3425	3830	4180	4585	5050	5455	5800
30	2425	2860	3295	3665	4100	4475	4910	5405	5840	6210
10 LT	3035	3580	4125	4590	5135	5600	6145	6765	7310	7775
10 HT	2425	2860	3295	3665	4100	4475	4910	5405	5840	6210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.