DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 41

TIRE SIZE	**29.5 R 25**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	CAMIÃO BASCULANTE / TRATOR DE ESTEIRA / CARREGADORA / DUMPER ARTICULADO
VERSÃO	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	200 B ; 208 A2

DIMENSÕES US STANDARD

CÓDIGO USA	94039852	**RIM REC**	25.00/3.5
OD (IN)	73.3	**TRA CODE**	E4/L4
SLR (IN)	32.7	**STAR RATING**	★★/★
RC (IN)	216.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	--

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..