


# AS 504

<b>TIRE SIZE</b>	<b>10.0/80 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	109 A8
<b>LI/SS FREE ROLLING</b>	121 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	270	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	730	<b>RIM ALT</b>	7.0
<b>SLR (MM)</b>	335	<b>ECE</b>	E11-106R-006010
<b>RC (MM)</b>	2233		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.90
10 FR	2030
25 FR	1725
30 FR	1625
40 FR	1450
10 DW	1440
25 DW	1225
30 DW	1155
40 DW	1030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.