


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 710/70 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	715	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	2061	<b>RIM ALT</b>	DW 23 B; DW 24 B
<b>SLR (MM)</b>	909	<b>ECE</b>	E11-106R-006266
<b>RC (MM)</b>	6182	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4
70	3960	4545	5220	5895	6565	7240	7915	8415
<b>FROM 65 TO 40</b>	4350	4995	5735	6475	7215	7955	8695	9250
30	4435	5095	5850	6605	7360	8115	8870	9435
20	4525	5195	5965	6735	7505	8275	9045	9620
10	4785	5495	6310	7125	7940	8755	9565	10175
<b>UPTO 30 CYC</b>	4935	5670	6510	7350	8190	9030	9870	10495
<b>UPTO 15 CYC</b>	5890	6770	7770	8775	9775	10780	11780	12530
<b>UPTO 10 CYC</b>	6460	7420	8520	9615	10715	11815	12915	13735
<b>10HT</b>	4435	5095	5850	6605	7360	8115	8870	9435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.