

AW 702

| | |
|---------------------------|--|
| TIRE SIZE | 10.0/80 - 12 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE |
| VERSÃO | SPECIAL |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 121 A8 |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 264 | RIM REC | 9.00 |
| OD (MM) | 710 | RIM ALT | 7.0 |
| SLR (MM) | 317 | ECE | E11-106R-004353 |
| RC (MM) | 2144 | PR | 10 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.90 |
|-------------------|-------------|
| 10 FR | 2030 |
| 25 FR | 1725 |
| 30 FR | 1625 |
| 40 FR | 1450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.