

AS 504

TIRE SIZE	7.5L - 15
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	97 A8
LI/SS FREE ROLLING	109 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019397	RC (IN)	89.8
SW (IN)	8.3	RIM REC	6 LB
OD (IN)	30.1	RIM ALT	5 K; 5½ J; 5½ K
SLR (IN)	13.9	ECE	E11-106R-004238

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	3170
15 FR	2700
20 FR	2550
25 FR	2270
5 DW	2250
15 DW	1920
20 DW	1810
25 DW	1610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.