


FLOTATION 648

TIRE SIZE	350/65 - 22.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	139 A8/135 B
LI/SS FREE ROLLING	151 A8/147 B



DIMENSIONS US STANDARD

USA CODE	94030644	RC (IN)	120.8
SW (IN)	14.1	RIM REC	AG 11.75
OD (IN)	40.6	ECE	E11-106R-004551
SLR (IN)	17.8	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	44	58	73
5 FR	6240	7900	9350	10650
10 FR	5610	7110	8420	9580
20 FR	4980	6320	7480	8520
25 FR	4450	5640	6680	7610
30 FR	4010	5080	6010	6780
5 DW	4390	5560	6590	7500
10 DW	3950	5000	5930	6750
20 DW	3510	4440	5270	6000
25 DW	3130	3970	4710	5360
30 DW	2820	3570	4230	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.