


AGRIMAX RT 600

IF 1250/50 R 32

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STEEL BELTED
TIRE TYPE	TL
	201 B



UNDEFINED IS STANDARD

SW (MM)	1247	RIM REC	DH44B/1.3 (multi-piece)
OD (MM)	2063	ECE	E11-106R-006958
SLR (MM)	897	SRI	975
RC (MM)	6136		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	6525	7395	9280	10295	11455	12325	13485	14500	---	---
40	7115	8065	10120	11225	12490	13435	14700	15805	---	---
30	7615	8630	10830	12010	13365	14380	15735	16915	---	---
10 LT	9535	10805	13560	15040	16735	18005	19700	21180	---	---
10 HT	7615	8630	10830	12010	13365	14380	15735	16915	---	---
UPTO 10 CYC WITH FRONT LOADER	---	11960	15320	16795	19485	21365	23380	25395	25800	26870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.